

ROTARY CUTTERS

FEATURES

Ideal for tractors 15 – 60 hp

3-point hitch: Category 1

Quick hitch compatible



Quickly cut down weeds, brush and your list of chores.

Yanmar rotary cutters easily handle small limbs and branches so you can clear your way with ease. With an included stump jumper, the cutters avoid damage by lifting the mower over rocks and other obstacles. These implements are made of thick steel and will last season after season.

INNOVATIVE DESIGN AND TECHNOLOGY



FULL-LENGTH SKID SHOES

are a standard feature, allowing cutter to glide easily over rough terrain.



STANDARD REAR METAL GUARDS

to prevent flying debris.



MODEL	YRC104R	YRC104SCR	YRC205R	YRC205SCR	YRC206R	YRC206SCR
Driveline Protection Options	Shear Pin	Slip Clutch	Shear Pin	Slip Clutch	Shear Pin	Slip Clutch
Weight	463 lbs.		530 lbs.		623 lbs.	
Hitch Cat. / Type	Category 1					
Cutting Width (in.)	48"		60"		72"	
Overall Width (in.)	51"		64"		75"	
Overall Length (Including Tailwheel) (in.)	77"		86"		93"	
Deck Height (in.)	7.5"					
Cutting Height Range (in.)	1.5-9"					
Cutting Capacity	up to 1"					
Tractor Horsepower	18-45		20-50		25-60	
Power Take-Off Speed	540					
Gearbox	45 hp cast iron housing, precision forged steel gears					
Gearbox Lubrication	EP 80-90W gear oil					
Gearbox Lubrication Capacity	23 ounces					
Deck Material Thickness	12 Ga.					
Stump Jumper	1/8" Thick, Round 22.3" pan-type					
Blades	1/2"x3" Heat Treated Free Swinging w/ suction lift					
Blade Tip Speed	9,982 ft./min.		12,478 ft./min.		14,974 ft./min.	
Driveline	ASAE Cat 4 Shear Bolt Protection					
Tailwheel	15" Laminated Tire					
Safety Guards	Optional Rubber Front/ Standard Metal Rear					
Blade Bolt Size	42mm socket					
Shear Bolt	1/2" x 3-1/2" Grd 2 Hex Bolt					
Castle Nut on Gearbox	38mm socket					

Yanmar has a corporate policy of continuous product improvement and development; therefore, data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manuals. Before operating a machine, read, understand, and follow all instructions in the manual and on the machine. Yanmar disclaims all representations, express or implied, or any liability from the use of this publication.