



SINGLE-SPINDLE

ROTARY CUTTERS

FEATURES

Ideal for tractors 15 – 50 hp

3-point hitch: Limited CAT 1 & CAT 1

Quick change pins

3-year limited gearbox warranty

Quickly cut down weeds, brush and your list of chores.


Whether you're clearing brush along miles of fence line, maintaining a roadway or just keeping weeds in check in an orchard or on a large property, these single-spindle rotary cutters sized for compact tractors help you make short work of anything that's growing where you don't want it to. Each features a rugged frame, a smooth, slope-top deck and quick-change blades built to easily handle the toughest conditions.

INNOVATIVE DESIGN AND TECHNOLOGY




FULL-LENGTH SKID SHOES

are a standard feature, allowing cutter to glide easily over rough terrain.



OPTIONAL CHAIN SHIELDING



MODEL	LOW-HP DUTY			STANDARD DUTY	
	YRC48	YRC60	YRC72	YRC720B	YRC840
Tractor PTO HP	15	18	21	30-65	35-90
Hitch Cat. / Type	Cat1 / clevis				Cat1&2
Cutting Width (in.)	48	60	72	72	84
Transport Width (in.)	53.5	65.5	72.5	72.5	89.5
Maximum Overall Length (in.)	92	104	116	116	128
Deck Length (in.)	58	70	84	84	96
Cutting height range (in.)	2-9"			1-9"	
Cutting Capacity (in.)	1"			2"	
Gearbox HP	50			75	90
Gearbox output shaft diameter (in.)	1.57				2
Blade tip speed (fpm)	13,100	13,620	14,340	14,963	15,086
Deck side depth (in.)	7"			9.5"	
Approximate Weight* (lbs.)	410	494	575	828	1084
Blade dimensions (in.)	0.5 x 3			(2) 0.38 x 3	(2) 0.5 x 3
Blade carrier	Oval stump jumper				Round
Blade mount system	Quick change pins				
Blade pin diameter (in.)	1.5				
Cutting deck thickness	11-Gauge			10-Gauge	
Safety-shielded driveline	Cat 3				Cat 4
Driveline protection	shear-pin or slip-clutch			slip-clutch	
Frame & Deck Support	3/8" rails			3 x 4" full length structural beams	
Tail Wheel	4 x 16 laminated				
PTO Speed (RPM)	540				
Quick Hitch Compatible	Yes				
Cutting Area Shielding	belt standard / Chain shielding optional				

Yanmar has a corporate policy of continuous product improvement and development; therefore, data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manuals. Before operating a machine, read, understand, and follow all instructions in the manual and on the machine. Yanmar disclaims all representations, express or implied, or any liability from the use of this publication.