DIESEL SEMI-CAB

- 4WD
- Built-in front windshield
- Standard wiper system
- Rear window protection
- Front grill guard
- Electric power steering
- Automotive tail lights, turn signals and flashers
- Digital instrument panels
- Ample storage space
- Side-adjustable comfort seating



LEARN MORE AT YANMARUTV.COM

nplied, or any liability from the use of this pub

Adairsville, GA 30103

ANMAR Am

101 International Pkw 770.877.9894 www.yanmaruty.com

R

BRAHMA



bre data, specifications, and warranty are subject to change without any advance notice. tition and the actual equipment. Equipment components produced by other manufacturers intended as an endorsement of that particular equipment or its suitability. Inspect equipment used or relied upon as a substitute for the safety and use information that is published in the tructions of the manual and on the machine. YANMAR disclaims all representations, express or



DIESELUTVs





SLIDE ADJUSTMENT RECLINING BUCKET SEATS WITH WEIGHT ADJUSTMENT







| KEY FEATURES | SEMI-CAB |
|--|----------|
| 2WD/4WD Rear Differential Lock (Turf Mode) | • |
| Electronic Power Steering | • |
| Dual-Range (High/Low Drive & Reverse) | • |
| 26" Tires on 14" Wheels (Aluminum) | • |
| Adjustable Suspension | • |
| 2.9 ³ ft. Front Storage | • |
| 8.6 ³ ft. Under Seat Storage | • |
| Cup Holders | • |
| Front Guard | • |
| Elevate Engine/ CVT Air Intake | • |
| Front Receiver Hitch | • |
| Rear Receiver Hitch | • |

| N - | | - | |
|------------|---|---|--|
| | _ | | |
| | | | |

DASHBOARD CONTROLS

NIDEE

TILTING CARGO BED



UNDER-SEAT STORAGE

FRONT STORAGE



HYDRAULIC DISC BRAKES





L STEEL CARGO BEDEOX

| ТҮРЕ | | Liquid-cooled 4 stroke, 3-cylinders | |
|-------------------------------|--------------|--|--|
| ENGINE | DISPLACEMENT | 993cc | |
| | НР | 24 | |
| Түре | | Diesel | |
| FUEL | | 10.6 gal. | |
| $L \times W \times H$ | | 134 × 65 × 78 in. | |
| GROUND CLEARANCE | | 12.2 in. | |
| DIMENSIONS CARGO BED CAPACITY | | 1000 lbs. / 17.13 ft. / Holds standard 48" pa | |
| TOWING CAPACITY (REAR) | | 2000 lbs. | |
| MAX. PAY LOAD | | 1389 lbs. | |
| TIL | TBED | Manual = Standard Only Manual | |
| RECEIVER HITCH | | Front & Rear = 2" Standard | |
| TIE-DOWN POINTS | | 16 integrated mounting points on the bed rail and 15 tie-down hooks | |
| TRANSMISSION | | CVT | |
| DRIVE TRAIN | | 2WD/ 4WD, Dual mode rear differential with differential lock | |
| MAX. PASSENGER | | 1 Row = 2 Passengers | |
| TRANSMISSION DRIVE TRAIN | | and 15 tie-down hooks CVT 2WD/ 4WD, Dual mode rear differentia with differential lock | |

ility Task Vehicles (UTVs) can be hazardous to operate. Improper use can cause severe injury or death. Each rider must be able to sit with their backs against the seat, feet flat on the floor and hands on the handholds/steering wheel. Each rider must read and understand the Operator's Manual before riding, Follow all instructions and warnings. Avoid abrupt maneuvers, paved surfaces, hard acceleration when turning, and side hilling; slow down before entering a turn. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Never carry a passenger in the cargo box or exceed seating capacity on a UTV. Never of a cohol or drugs. Do not shoot from or lean firearms or bows against the UTV. YANMAR recommends that all riders take a training course. For safety training information or UTV training visit http://rohva.org. All materials and specifications are subject to change without notice. All specifications, claims and information contained within are based on current knowledge and readily available information and material as of 02/28/2023. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may not be available at all dealerships. YANMAR disclaims and warranties, express or implied, or any liability from the use of this brochure.

24.2HP, 993CC, Final Tier 4

Compliant, Liquid-cooled, Four Cycle YANMAR Diesel Engine

- Naturally aspirated, incline 3-cylinder
- Excellent fuel efficiency and range
- Indirect fuel injection
- High-stiffness cylinder block and gearcase
- High-flow water pump and optimized water jacket
- In-line mechanical fuel pump

DIESEL UTV **MAINTENANCE KIT** #KIT-D-UTV

| PART NUMBER | QTY | COMPONENT DESCRIPTION |
|----------------|-----|-----------------------------|
| 119305-35151 | 1 | Oil Filter Element |
| S1050 | 3 | 10W50 SYN QT 12PK |
| 1NF002-00020 | 1 | Element, Oil Cleaner |
| 119810-55650 | 1 | Water Separator Filter |
| 25152-003500 | 1 | V-Belt |
| 1NF050-00030 | 1 | Element, Air Filter* |
| 171081-55910 | 1 | Fuel Filter Water Separator |
| | | |

CVT Drive System

Smooth transition at low speeds that reduces wear on the belt and enables speed control.

FACTORY PACKAGES

PURPOSE-BUILT UTVs

• ENSURES QUALITY • COST-EFFECTIVE • SPECIALIZED/CUSTOM ASSEMBLY

Jobsite with Paved Tire Package Jobsite Package Front LED Light Package SEMI-CAB SEMI-CAB SEMI-CAB • 40" Front LED Light Plastic Roof Plastic Roof Strobe Light Strobe Light Reverse Alarm Reverse Alarm Cargo Bed Mat Cargo Bed Mat Universal Key Universal Key Durable Paved Tire Kit

| LED Light Package | Trailer Package | Ranch Package |
|--|---|--|
| SEMI-CAB 40" Front LED Light 2 × 6" Rear LED Light Package | SEMI-CAB Trailer Harness Kit Silver Sticker Package | SEMI-CAB Trailer Harness Kit LED Light Package |

| Front Winch Package | Professional Package | Turf Working Package |
|---|--|--|
| SEMI-CAB Trailer Harness Kit Front Winch Guard 3,000 lbs. Warn Winch | SEMI-CABFront Winch PackageLED Light Package | SEMI-CAB Cargo Bed Mat Turf Tire Kit |

LEARN MORE AT YANMARUTV.COM

