

NEW

SM240 / SM240H / SM475



# ELEVATE YOUR EXPERIENCE

with the next generation of lift capacity





# LEGENDARY TRACTORS TO POWER YOUR EXTRAORDINARY LIFE





Our story began with one simple and powerful tenet: “To conserve fuel is to serve mankind”. Everything we create is based on our commitment to quality—providing efficient, sustainable solutions for stewards of the land.

We understand that the choices you make today will have a lasting effect on future generations, which is why we are **built better to last longer.**





# SM240 / SM240H

Offering Yanmar craftsmanship and comfort in a compact, agile body, the SM240 line provides powerful multi-functional capability with the option of a clutch-less transmission. Enrich your experience with a higher standard in tractor performance.

## TRANSFORMATIONAL PERFORMANCE

With a Yanmar engine providing maximum torque at lower RPMs, it tackles heavy loads and implements. Enjoy one of the highest lift capacities on the market.



Backhoe is a factory-ordered option

## SM240 / SM240H

### COMPACT UTILITY TRACTOR SPECIFICATIONS

Ideal Acreage	15-45
Engine HP	36.9
Loader Lift Capacity	2,116 LBS.
Transmission	SM240 Synchro Shuttle SM240H Hydrostatic

### WARRANTY COVERAGE

Tractor*	24 months or 2,000 hours (whichever comes first)
Powertrain*	10 years or 3,000 hours (whichever comes first)

\*for non-commercial, home and residential use only

POWERTRAIN	SM240	SM240H
Engine Manufacturer	Yanmar	Yanmar
Engine Gross Power	36.9 HP (27.5 kW)	36.9 HP (27.5 kW)
PTO Power	28.2 HP (21.0 kW)	27.5 HP (20.5 kW)
Rated Engine Speed	3,000 RPM	3,000 RPM
Clutch	Dry Single Plate	–
CAPACITIES		
Fuel Tank	9.0 gal. (34 L)	9.0 gal. (34 L)
DRIVETRAIN		
Transmission Type	Synchro Shuttle	Hydrostatic
Rear Differential Lock	Foot Pedal Engagement	Foot Pedal Engagement
2WD/4WD Engagement	Selectable	Selectable
PTO Type	Independent	Independent
PTO Control	Electric & Hydraulic	Electric & Hydraulic
Rear PTO Speed	540 RPM	540 RPM

### HYDRAULICS

Pump Capacity (Steering) @ Rated RPM	4.4 GPM (16.66 L/min)
Pump Capacity (Implement) @ Rated RPM	6.1 GPM (23.09 L/min)
Pump Capacity (Total) @ Rated RPM	10.5 GPM (39.75 L/min)
3-Point Hitch Category	1
3-Point Lift Capacity (Std.)	2,639 lbf. (1,197 kgf)
3-Point Lift Capacity at 24" (61 cm)	1,558 lbf. (707 kgf)
Remote Valves	Optional (1 or 2)
3rd Function Valve	Optional

### DIMENSIONS AND WEIGHT

Minimum Ground Clearance	12.8" (325 mm)
Total Weight	3,020 lb. (1,370 kg)

### FRONT END LOADER

#### RL505

Maximum Lift Height to Pivot Pin	101.5" (2,578 mm)
Lift Capacity to Maximum Height at Pivot Pin	2,116 lb. (960 kgf)
Breakout Force at Ground Level Pivot Pins	3,435 lb. (1558 kgf)



## EXCEPTIONAL QUALITY

Providing extraordinary durability and reliability plus an ergonomic operator station, it exceeds industry standards in every way. It's a legacy your family will cherish for generations.



## ADVANCED TECHNOLOGY AND DESIGN

From the convenient, foldable ROPS to the joystick-operated front-end loader, every aspect has been designed to enhance your land-working experience.







## **TRANSFORMATIONAL PERFORMANCE**

Specializing in precision tasks like trenching, it ensures greater impact with fewer passes. And its high-capacity fuel tank means it can tackle medium- to heavy-duty tasks for extended durations.



## **ADVANCED TECHNOLOGY AND DESIGN**

Equipped with a clutch-less power shuttle transmission for effortless operation. Adjust the power steering and tilt, all implements, and a joystick-controlled loader—all without leaving your seat.



# SM475

Harnessing the highest HP Yanmar offers, the SM475 gives you the confidence to power through any job. Its purposeful design is intuitive to your needs so you can concentrate on the land.

## EXPERIENCE LUXURY

Boasting a dual-entry deluxe cab, advanced climate control, ergonomic operator station with digital command hub, and an immersive audio system, empowering you to work your land in the utmost comfort.



## SM475

### COMPACT UTILITY TRACTOR SPECIFICATIONS

Ideal Acreage	35-75
Engine HP	74
Transmission	Power Shuttle
Luxury Cab with AC/heat and more	

#### WARRANTY COVERAGE

Tractor*	24 months or 2,000 hours (whichever comes first)
Powertrain*	10 years or 3,000 hours (whichever comes first)

\*for non-commercial, home and residential use only

#### POWERTRAIN

Engine Manufacturer	Deutz
Engine Gross Power	74 HP (55.4 kW)
PTO Power	64.1 HP (47.8 kW)
Rated Engine Speed	2,200 RPM
Clutch	Wet Multi Plate

#### CAPACITIES

Fuel Tank	23.8 gal. (90 L)
-----------	------------------

#### DRIVETRAIN

Transmission Type	Power Shuttle
Rear Differential Lock	Foot Pedal Engagement
2WD/4WD Engagement	Selectable
PTO Type	Independent
PTO Control	Electric/Hydraulic
Rear PTO Speed	540 RPM

#### HYDRAULICS

Pump Capacity (Steering) @ Rated RPM	5.8 GPM (22 L/min)
Pump Capacity (Implement) @ Rated RPM	10.3 GPM (39.1 L/min)
Pump Capacity (Total) @ Rated RPM	16.1 GPM (61.1 L/min)
3-Point Hitch Category	Category 2
3-Point Lift Capacity (Std.)	5,115 lbf. (2,320 kgf)
3-Point Lift Capacity at 24" (61 cm)	3,418 lbf. (1,550 kgf)
Remote Valves	Standard (2)
3rd Function Valve	Optional

#### DIMENSIONS AND WEIGHT

Minimum Ground Clearance	18.3" (465 mm)
Total Weight	6,052 lb. (2,745 kg)

#### FRONT END LOADER

#### RL705

Maximum Lift Height to Pivot Pin	133.8" (3,398 mm)
Lift Capacity to Maximum Height at Pivot Pin	3,325 lb. (1,508 kgf)
Breakout Force at Ground Level Pivot Pins	5,485 lb. (2,488 kgf)





NEW

SM240 / SM240H / SM475



## LIFT MORE WITH A LONGER WARRANTY

**BUILT BETTER.  
BACKED LONGER.**  
Industry-leading warranty.

## BEST IN CLASS

- #1 quality ranking technology
- SM240s offer one of the highest lift capacities of any compact tractor on the market
- SM475 offers the highest HP found in a U.S. Yanmar tractor

Find your local dealer at [yanmartractor.com/dealer-locations](https://yanmartractor.com/dealer-locations) or by visiting:

YANMAR America Corporation  
101 International Pkwy, Adairsville, GA 30103  
770.877.9894

[www.YANMARtractor.com](https://www.YANMARtractor.com)

The information in this brochure is accurate as of the date of printing and subject to change. All rights reserved by and belong to YANMAR®.  
©2024 YANMAR America Corporation. YT21-170 11/03

YANMAR has a corporate policy of continuous product improvement and development; therefore data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating a machine, read, understand, and follow all instructions of the manual and on the machine. YANMAR disclaims all representations, express or implied, or any liability from the use of this publication.



<https://www.facebook.com/yanmartractoramerica>



<https://www.instagram.com/yanmaramerica>



<https://www.linkedin.com/yanmaramerica>



<https://www.youtube.com/user/yanmarusa>



PLANTING / HARVESTING / MOWING / DIGGING / GRADING / MATERIAL HANDLING / SNOW REMOVAL