



STANDARD DUTY
REAR-MOUNT

FINISH MOWERS

FEATURES

Deep 4.6-inch deck, baffling and unique rear discharge design ensures exceptional material distribution

Spring-loaded idler arms automatically maintain the correct tension on our custom-made belts

Tubular caster arms and heavy, tall deck rail supports (4.5-inches) for increased strength and durability

Turn acres of grass into well-groomed acres of lawn.

There's nothing more rewarding than a lawn that's finely groomed like a country club fairway. Especially when it doesn't take all day to make it look that way. That's why our finish mowers are engineered for speed, precision and enduring quality. The innovative rounded-front, tapered-side, rear-discharge deck allows you to reduce trim and mow with better maneuverability. And the heat-treated, alloy steel blades always give you a beautiful, high-precision cut on any type of grass.

YFM54 shown with optional chain shielding*

*All YFM Series finish mower models pass all applicable safety standards for thrown object and blade contact without chain shielding. However, if these units will be used in areas where the possibility of thrown objects could be hazardous to persons or property, it is strongly recommended that optional chain shielding be used for extra protection.

INNOVATIVE DESIGN AND TECHNOLOGY



ROUNDED FRONT CORNERS

and tapered deck sides improve maneuverability and grass discharge.



BOX-STYLE CONSTRUCTION

for superior deck strength.



Yanmar Finish Mowers Specifications

VEGETATION MANAGEMENT

MODEL	STANDARD DUTY			MEDIUM DUTY		
	YFM54	YFM60	YFM72	YFM600	YFM720	YFM840
Tractor PTO HP Range	15-25	15-35	20-35	15-40	20-40	25-49
Hitch/Quick Hitch Compatible	Limited Cat 1/No	Cat 1/Yes				
Cutting Width (in.)	54	60	72	69	72	84
Weight (lbs)	401	503	603	653	719	830
Cutting Height Range (in.)	1-4.5			1-5.5		1-4.25
Overall Width (in.)	55	61	73	62	74	86
Deck Material Thickness	10-gauge			8-gauge		
Side Skirt (in.)	10-gauge x 4.6 deep	8-gauge x 4.6 deep		8 gauge x 5.375 w/ .5625 diam. skid rod bumper		
Gearbox HP Rating	25	35		60		
Blade Tip Speed (FPM)	16,200	18,030	18,000	18,100	18,000	17,900
Blade Spindles/Bearings	3 cast iron housings/greasable ball bearings			3 cast iron housings/greasable tapered roller bearing		
Tractor PTO Speed (RPM)	540					
Driveline Size	Cat 3					
Belt	B-Section Kevlar®			B-Section Kevlar® with clutching cover		
Belt Adjustment	Spring-loaded idler					
Rear Chain Shielding	Optional					
Mower Warranty	1 year residential or 90 day commercial			1 year		
Gearbox Warranty (Limited)	3 year homeowners or 1 year commercial			6 years		
Wheels	pneumatic rubber wheels or solid rubber wheels			solid rubber wheels		